



PROLINE

RESIDENTIAL GAS SHEET

Model Number	Gallon (liter) Capacity	btu input natural gas	btu input propane	GPH Rec. 90° F Rise natural	GPH Rec. 90° F Rise propane	EF	Height to top of Vent inch & (mm)	Jacket Diameter inch & (mm)	Height to top of heater inch & (mm)	Vent Diameter inch & (mm)	Height to side T&P inch & (mm)	Approx. Shipping Weight Lbs & (Kg)
PROLine™ Natural Gas Side-mounted factory -installed T&P valve Limited tank and parts warranty Handhole Cleanout (100T88 only)												
G61-30S30-3NV	30 (114)	30,000	30,000	30.4	30.4	0.58	48 1/2 (1232)	18 (457)	45 1/4 (1149)	3 (76)	39 (991)	95 (43.1)
G61-30T33-3NV	30 (114)	33,000	33,000	33.5	33.5	0.58	59 1/2 (1511)	16 (406)	56 (1422)	3 (76)	49 1/2 (1257)	98 (44.5)
G61-40S33-3NV	40 (151)	33,000	33,000	33.9	33.9	0.56	50 1/4 (1276)	20 (508)	47 (1194)	3 (76)	41 1/2 (1054)	117 (53.1)
G61-40T34-3NV	40 (151)	34,000	34,000	34.9	34.9	0.57	60 1/4 (1530)	18 (457)	57 (1448)	3 (76)	50 1/2 (1283)	114 (51.8)
G61-40S40-3NV	40 (151)	40,000	40,000	40.5	40.5	0.55	51 3/4 (1314)	20 (508)	48 1/2 (1232)	3 (76)	42 1/4 (1073)	127 (57.7)
G61-40T40-3NV	40 (151)	40,000	40,000	42.2	42.2	0.56	61 1/2 (1562)	18 (457)	58 1/4 (1480)	3 (76)	51 3/4 (1314)	124 (56.3)
G61-50T40-3NV	50 (189)	40,000	40,000	40.5	40.5	0.55	60 1/4 (1530)	20 (508)	57 (1448)	3 (76)	50 1/2 (1283)	146 (66.3)
G61-50T50-4NV	50 (189)	50,000	50,000	50.7	50.7	0.53	60 1/4 (1530)	20 (508)	57 (1448)	4 (102)	50 1/2 (1283)	146 (66.3)
G62-50T63-4NV	50 (189)	63,000	60,000	63.9	60.8	0.53	63 (1600)	22 (559)	59 1/2 (1511)	4 (102)	53 1/4 (1353)	172 (78.1)
G62-75T75-4NV	75 (284)	75,100	75,100	76.1	76.1	NA	63 1/2 (1613)	26 (660)	60 (1524)	4 (102)	53 1/4 (1353)	243 (110.3)
G62-100T88-4NV	100 (379)	88,000	88,000	89.2	89.2	NA	68 3/4 (1746)	28 1/4 (718)	65 1/8 (1654)	4 (102)	59 1/4 (1505)	392 (178.0)
PROLine™ Natural Gas Self-Cleaning Side-mounted factory-installed T&P valve Limited tank and parts warranty Self-Cleaning LimeFighter™												
G91-40S33-3NV	40 (151)	33,000	33,000	33.9	33.9	0.56	50 1/4 (1276)	20 (508)	47 (1194)	3 (76)	41 1/2 (1054)	117 (53.1)
G91-40T34-3NV	40 (151)	34,000	34,000	34.9	34.9	0.57	60 1/4 (1530)	18 (457)	57 (1448)	3 (76)	50 1/2 (1283)	114 (51.8)
G91-50T35-3NV	50 (189)	35,000	35,000	36.4	36.4	0.55	60 1/4 (1530)	20 (508)	57 (1448)	3 (76)	50 1/2 (1283)	138 (62.7)
PROLine Plus™ Self-Cleaning Side-mounted factory-installed T&P valve Easy lighting Piezo ignitor Self-cleaning LimeFighter™ Limited tank and parts warranty Brass drain valve												
G122-40T40-3NMV	40 (151)	40,000	40,000	42.2	42.2	0.61	61 1/2 (1562)	20 (508)	58 1/4 (1480)	3 (76)	51 3/4 (1314)	132 (59.9)
G122-50T35-3NMV	50 (189)	35,000	35,000	36.4	36.4	0.61	60 1/4 (1530)	22 (559)	57 (1448)	3 (76)	50 1/2 (1283)	152 (69.0)
G122-50T63-4NMV	50 (189)	63,000	60,000	63.9	60.8	0.53	63 (1600)	22 (559)	59 1/2 (1511)	4 (102)	53 1/4 (1353)	172 (78.1)
G122-75T75-4NMV	75 (284)	75,100	75,100	76.1	76.1	NA	63 1/2 (1613)	26 (660)	60 (1524)	4 (102)	53 1/4 (1353)	243 (110.3)