

## MOBILE HOME ATMOSPHERIC VENT



### GAS CONTROL CONVERTIBLE FOR NATURAL AND PROPANE GAS

- For flexibility to meet the varying needs of manufactured housing installations.

### GREEN CHOICE® GAS BURNER

- Patented eco-friendly burner design reduces NOx emissions by up to 33% and complies with Low-NOx emission requirements of less than 40 ng/J.

### COREGARD™ ANODE ROD

- Our anode rods have a stainless steel core that extends the life of the anode rod allowing superior tank protection far longer than standard anode rods.

### BLUE DIAMOND® GLASS COATING

- Provides superior corrosion resistance compared to industry standard glass lining.

### ENHANCED-FLOW BRASS DRAIN VALVE

- Our residential water heaters have a solid brass, tamper resistant, enhanced-flow, ball type, drain valve.
- Uses a standard female hose fitting that allows for fast and easy draining during maintenance.
- Designed for easy operation, this valve includes an integral screwdriver slot that features a ¼ turn (open/close) radius, which not only permits full straight-through water flow but also a quick and positive shut off.

### CODE COMPLIANCE

- Meets UBC, CEC and HUD National Codes.
- Meets the thermal efficiency and standby loss requirements of the U. S. Department of Energy and current edition of ASHRAE/IESNA 90.1.
- Complies with the Federal Energy Conservation Standards effective April 16, 2015, in accordance with the Energy Policy and Conservation Act (EPCA), as amended.

### COMPLIES WITH HUD STANDARDS FOR MANUFACTURED HOUSING INSTALLATION

### CSA CERTIFIED AND ASME RATED T&P RELIEF VALVE

### MAXIMUM HYDROSTATIC WORKING PRESSURE 150 PSI

### 6-YEAR LIMITED TANK AND PARTS WARRANTY

- For complete information, consult written warranty or go to [www.americanwaterheater.com](http://www.americanwaterheater.com).






# Residential Gas Water Heater

Model Number	Gallon Capacity	First Hour Rating Gallon	Energy Factor	Recovery @ 90°F Rise Gallon Per Hour	Btu Input Per Hour Natural Gas	Btu Input Per Hour Propane	Dimensions in Inches						Approx. Shipping Weight (lbs)	
							Insulation	A	B	C	D	E		Draft Hood Outlet
MHG62-30T30	30	54	0.63	31	30,000	29,000	2	60	56-1/2	17-3/4	11-1/4	49-1/4	3 or 4	129
MHG62-40T40	40	71	0.62	41	40,000	36,000	2	62	58-1/2	19-3/4	11-1/4	51-3/4	3 or 4	153

All models ship from the factory for use with natural gas, a complete propane burner is supplied for converting to propane gas.  
 All models are certified from sea level to 10,100 ft. elevation.  
 Dimensions and specifications subject to change without notice, in accordance with our policy of continuous product improvement.



For technical information call (800) 999-9515. American Water Heaters reserves the right to make product changes or improvements without prior notice.