

## HIGH EFFICIENCY HGG SERIES COMMON VENTING KIT

### BENEFITS

- Fewer wall penetrations than standard single-unit venting
- Reduced install cost with easy to install non-powered kits
- Flexibility of using PVC or polypropylene vent material

### SPECIFICATIONS

- Approved for use with 120, 150, 199, 250, 300, 400 and 500 High Efficiency HCG Series models
- Approved for side wall (horizontal) vent applications only
- 50 Feet maximum equivalent length of straight pipe common vent and elbows
- Direct vent configuration only
- Maximum of two water heaters can be common vented

- One kit per water heater required, chose from PVC or polypropylene, model input size
- Kits include backflow preventer plus intake and exhaust adapters. Piping and termination field supplied.
- Each wall penetration requires a 7" hole through the structure
- Common vent kits are UL listed





# Commercial Gas Accessories

Kit	Description
9009152005	PVC Common Vent Kit, 120 – 250 Models
9009227005	PVC Common Vent Kit, 300 – 500 Models
9009132005	Polypropylene Common Vent Kit, 120 -250 Models
9009226005	Polypropylene Common Vent Kit, 300 - 500 Models

Installations must comply with all national, state and local codes.

See kit instructions and corresponding water heater manual for detailed installation instructions and additional information.

**For technical information call (800) 999-9515. American Water Heaters reserves the right to make product changes or improvements without prior notice.**