



# TANKLESS WATER HEATERS



[www.americanwaterheater.com](http://www.americanwaterheater.com)



# Non-Condensing Residential/ Commercial Gas

- ENERGY STAR® Qualified
- Category III Stainless Steel Venting
- Indoor Models Include Remote Control and an Installed Power Cord as Standard Features
- Outdoor Models Include Remote Control as a Standard Feature
- Easy-Link up to 4 Units (GT-510 models only)
- Low NOx Emissions
- HRS35 Commercial-Grade Copper Heat Exchanger (GT-510 models only)
- 15 Year Limited Residential Heat Exchanger Warranty
- 10 Year Limited Commercial Heat Exchanger Warranty
- 5 Year Limited Parts Warranty

Model Number*	Type	BTU/h Input Natural/Propane		Energy Factor (EF)
		Minimum	Maximum	
GT-110-NI	Indoor	19,500	140,000	0.82
GT-310-NI	Indoor	11,000	190,000	0.82
GT-510-NI**	Indoor	11,000	199,000	0.82
GT-110-NE	Outdoor	19,500	140,000	0.82
GT-310-NE	Outdoor	11,000	190,000	0.82
GT-510-NE**	Outdoor	11,000	199,900	0.82

Model Number*	Hot Water Output (GPM)			Unit Weight (lbs.)
	Maximum	45°F Rise	70°F Rise	
GT-110-NI	6.6	5.1	3.3	33
GT-310-NI	8.0	6.9	4.4	38
GT-510-NI**	10.0	7.2	4.7	39
GT-110-NE	6.6	5.1	3.3	33
GT-310-NE	8.0	6.9	4.4	38
GT-510-NE**	10.0	7.2	4.7	39

\*For Propane, change the N to P in the model number when ordering: Example: GT-110-PI

\*\*Models can be installed in commercial applications, recirculation applications, and easy-link up to 4 units.



# High Efficiency Condensing Residential/ Commercial Gas

- Ultra-Low NO<sub>x</sub> Condensing Technology Provides Significant Energy Cost Savings - Unprecedented 0.95 Energy Factor
- ENERGY STAR® Qualified
- Indoor Models Have Integrated Controls & Diagnostics
- Outdoor Models Include Remote Control as a Standard Feature
- Power Direct Vent Design
- Complies with Lead Free Standards
- Primary Heat Exchanger is Constructed of HRS35 Commercial-Grade Copper
- Secondary Heat Exchanger Constructed of 316L Stainless Steel
- Easy-Link 4 Units and Multi-Link up to 20 Units (GT-540 models only)
- 15 Year Limited Residential Heat Exchanger Warranty
- 10 Year Limited Commercial Heat Exchanger Warranty
- 5 Year Limited Parts Warranty

Model Number*	Type	BTU/h Input Natural		Energy Factor (EF)
		Minimum	Maximum	
GT-240-NIH	Indoor	15,000	160,000	0.95
GT-340-NIH	Indoor	15,000	180,000	0.95
GT-540-NIH	Indoor	15,000	199,000	0.95
GT-340-NEH	Outdoor	15,000	180,000	0.95
GT-240-NEH	Outdoor	15,000	160,000	0.95
GT-540-NEH	Outdoor	15,000	199,000	0.95

Model Number*	Hot Water Output (GPM)			Unit Weight (lbs.)
	Maximum	45°F Rise	70°F Rise	
GT-240-NIH	6.6	6.6	4.3	58
GT-340-NIH	8.0	7.6	4.9	58
GT-540-NIH	10.0	8.4	5.4	59
GT-240-NEH	6.6	6.6	4.3	58
GT-340-NEH	8.0	7.6	4.9	58
GT-540-NEH	10.0	8.4	5.4	59

\*For Propane, change the N to P in the model number when ordering: Example: GT-240-PIH  
+Propane (LP) Gas minimum Btu/h is 13,000.



# Heavy-Duty Commercial Gas

- HRS35 Commercial-Grade Copper Heat Exchanger (Non-ASME Models)
- ASME Models Available
- 4" Category III Stainless Steel Venting (GT-710 models), 5" Category III Stainless Steel Venting (GT-910 models)
- Vertical or Horizontal Vent Installation
- Dual Combustion System for Added Reliability (GT-910 models)
- Combined Indoor/Outdoor Models
- Multi-Link up to 20 Units (GT-710 models)
- Multi-Link up to 10 Units (GT-910 models)
- 10 Year Limited Commercial Heat Exchanger Warranty
- 5 Year Limited Parts Warranty

Model Number*	BTU/h Input Natural/Propane		Thermal Efficiency
	Minimum	Maximum	
GT-710-NIE	24,000	240,000	82%
AGT-710-NIE***	24,000	240,000	82%
GT-910-NIE	15,000	380,000	80%
AGT-910-NIE***	15,000	380,000	80%

Model Number*	Hot Water Output (GPM)			Unit Weight (lbs.)
	Maximum	45°F Rise	70°F Rise	
GT-710-NIE	9.0	8.5	5.5	59
AGT-710-NIE***	9.0	8.5	5.5	59
GT-910-NIE	14.5	13.5	8.7	112
AGT-910-NIE***	14.5	13.5	8.7	112

\*For Propane, change the N to P in the model number when ordering:

Example: GT-710-PIE

\*\*\*ASME Models



# Ultra Low-NOx Non-Condensing Residential/ Commercial Gas

- ENERGY STAR® Qualified
- Category III Stainless Steel Venting
- Complies with Ultra-Low NOx Regulations
- Indoor Models Include Remote Control and an Installed Power Cord as Standard Features
- Outdoor Models Include Remote Control as a Standard Feature
- Easy-Link up to 4 Units (GT-510U models only)
- Multi-Link up to 20 Units (GT-510U models only)
- HRS35 Commercial-Grade Copper Heat Exchanger (GT-510U models only)
- 15 Year Limited Residential Heat Exchanger Warranty
- 10 Year Limited Commercial Heat Exchanger Warranty
- 5 Year Limited Parts Warranty

Model Number	Type	BTU Input Natural		Energy Factor (EF)
		Minimum	Maximum	
GT-110U-NI	Indoor	15,000	140,000	0.82
GT-310U-NI	Indoor	15,000	190,000	0.82
GT-510U-NI	Indoor	15,000	199,000	0.82
GT-110U-NE	Outdoor	15,000	140,000	0.82
GT-310U-NE	Outdoor	15,000	190,000	0.82
GT-510U-NE	Outdoor	15,000	199,900	0.82

Model Number	Hot Water Output (GPM)			Unit Weight (lbs.)
	Maximum	45°F Rise	70°F Rise	
GT-110U-NI	6.6	5.1	3.3	33
GT-310U-NI	8.0	6.9	4.4	37
GT-510U-NI	10.0	7.2	4.7	39
GT-110U-NE	6.6	5.1	3.3	33
GT-310U-NE	8.0	6.9	4.4	37
GT-510U-NE	10.0	7.2	4.7	39

# Rely on American.

Now more than ever before you can rely on American Water Heaters to provide a tankless gas water heater to meet your residential or commercial needs. With flow rates up to 14.5 GPM, our tankless water heaters provide continuous hot water when sized appropriately for your application needs. We offer a complete line of products from 140,000 to 380,000 BTU/h. Our tankless heaters are ENERGY STAR® qualified.

***Rely on American  
for all your  
water heating needs.***



500 Tennessee Waltz Parkway  
Ashland City, TN 37015  
[www.americanwaterheater.com](http://www.americanwaterheater.com)