

PROLINE® XE HIGH EFFICIENCY COMMERCIAL-GRADE RESIDENTIAL

PRESSURIZED COMBUSTION SYSTEM

- Exclusive and patented pressurized combustion chamber with an advanced blower distributes an optimum air-to-gas mixture pushing exhaust gases atmospheric gas product on the market with a .70 Energy Factor (EF).

INSTALLER-FRIENDLY

- Allows for easy replacement of standard atmospheric vent heaters.
- Easily connects to existing B-vent.
- Plugs into standard 110/120V outlet (10 foot power cord included).

24V ELECTRONIC CONTROLS

- Tighter differential for more consistent hot water delivery.

ELECTRONIC IGNITION

- The durable hot surface ignitor eliminates pilot relight issues (no standing pilot).

LCD USER INTERFACE

- Easy-to-read, eye level display. Simple temperature settings and adjustments. Service diagnostics are in plain text.

POWERED ANODE ROD

- Powered anodes are non-sacrificial, so they do not deplete over time. Additionally, they provide exceptional performance in all water conditions.

MEETS ENERGY-EFFICIENCY REQUIREMENTS FOR MOST GAS UTILITY REBATE PROGRAMS AND MEETS ENERGY STAR® REQUIREMENTS.

ENHANCED-FLOW BRASS DRAIN VALVE

- Our residential water heaters have a solid brass, tamper resistant, enhanced-flow, ball type, drain valve.
- Uses a standard female hose fitting that allows for fast and easy draining during

SELF-CLEANING DIFFUSER DIP TUBE

- Reduces lime and sediment buildup and maximizes hot water output. Made from long-lasting PEX cross-linked polymer.

GREEN CHOICE® GAS BURNER

- Patented Low NOx burner reduces emissions by up to 33% and complies with less than 40 ng/J requirements for Low NOx.

CSA CERTIFIED AND ASME RATED T&P RELIEF VALVE

CODE COMPLIANCE: UBC, CEC, SBCC, CABO, HUD, BOCA NATIONAL CODES, CURRENT EDITION ASHRAE/IES 90.1 AND 2004 NAECA STANDARDS

DESIGN-CERTIFIED BY CSA INTERNATIONAL

- According to ANSI Z21.10.1 - 4.1 CSA Standards governing storage-type water heaters.

6-YEAR LIMITED TANK/ 6-YEAR LIMITED PARTS WARRANTY

- For complete warranty information go to americanwaterheater.com.







COMMERCIAL-GRADE RESIDENTIAL GAS WATER HEATERS

Model Number	Gallon Capacity	First Hour Rating Gallons	Energy Factor (EF)	BTU Input Gallon Per Hour	Recovery @ 90°F Rise Gallon Per Hour	Dimensions in Inches										Approx. Shipping Weight (lbs)
						Foam Thickness	A	B	C	D	E	F	G	H	Draft Hood	
PCG6240T403NOV	40	70	0.70	40,000	43	2	61-3/4	58	20	13-1/4	8	51-1/2	23-1/4	25	3 or 4	157
PCG6250T403NOV	50	81	0.70	40,000	43	2	60-5/8	57-1/8	22	13-1/4	8	50-1/2	25-1/4	27	3 or 4	171

All dimension in inches.
 Recovery capacity based on actual performance tests.
 Water Connections – 3/4" on all models.
 Not available in LP gas (Propane).
 Certified for installations up to 10,100 ft. elevations.



FRONT VIEW



TOP VIEW

Maximum Hydrostatic Working Pressure: 150 PSI

For technical information call (800) 999-9515. American Water Heaters reserves the right to make product changes or improvements without prior notice.